

# CR RUBBER ROLLER

**HYPERROLLER**  
RUBBER ROLLER FOR YOUR INDUSTRY

Physical Properties	Values
Hardness Range (Shore A)	5-70
Abrasion Resistance	Good to Excellent
Tear Resistance	Good to Excellent
Load Bearing	Good
Hysteresis	Good
Resistance To denting	Fair
Maximum Working Temperature (°C)	140
Resiliency	Fair to Good
Solvent Resistance	Values
Acid (Concentrated)	Poor
Caustics (Concentrated)	Poor
Aliphatic Hydrocarbons	Poor to Good
Aromatic Hydrocarbons	Poor to Fair
Chlorinated Hydrocarbons	Poor
Ketones	Poor to Fair
Alcohol	Excellent
Esters	Poor to Fair
Environmental Performance	Values
Colorability	Fair
Flame Resistance	Fair to Good
Gas Permeability	Fair to Good
Odor	Fair to Good
Ozone Resistance	Good to Excellent
Oxidation Resistance	Good to Excellent
Radiation Resistance	Fair to Good
Steam Resistance	Fair to Good
Sunlight Resistance	Good to Excellent
Taste Retention	Fair to Good
Weather Resistance	Fair to Good
Water Resistance	Fair to Good



CONTACT US. TEL : 0 2408 2583-4 MB : 06 2151 5494

LINE@ @ptirubber

Email: [pti\\_sale2@hotmail.com](mailto:pti_sale2@hotmail.com) / [ptiproduct@hotmail.com](mailto:ptiproduct@hotmail.com)

Technical Engineer MB : 08 6307 7319

Website <https://hyper-roller.com>